

MPPT PV Optimization 600 Vdc Solar Charge Controllers

6 kW MPPT 100 600 (Part Number 865-1034)

4.8 kW MPPT 80 600 (Part Number 865-1032)



The MPPT 80 and MPPT 100 600 Vdc Solar Charge Controllers optimize the power from PV arrays for DC coupled solar and storage installations, with easy, flexible installation.

Optimum System Performance

- High power, 600 Vdc MPPT PV optimization and battery charge control
- Flexibility for oversized PV array power ratings up to 8.5 kW with the MPPT 100 or 6.8 kW with the MPPT 80
- High efficiency from PV to battery to grid, ideal for the self-consumption of solar energy
- Black start batteries from solar, providing maximum energy resilience for longer duration grid outages
- Harvest more energy with shade tolerant fast sweep MPPT algorithm

Flexible

- Flexible string sizing with a wide MPPT and PV operating voltage range
- Compatible with XW Pro and SW series hybrid inverters for a complete grid tied or off grid solar and storage solution

Easy to Install

- 2 string installations and smaller wire sizing with 600 Vdc PV arrays, allowing faster, lower cost installations
- No need for a combiner box with DC breakers or fuses
- Easy to install PV disconnect and NEC 2017 compliant rapid shutdown transmitter with the MPPT Disconnect RS accessory, UL1741 PVRSS certified

Compatible with Insight Energy Management

- Setup and configuration
- Remote monitoring & control with advanced data security
- Web and mobile app
- Multi-site management for installers



Insight Energy Management

Technical Specifications

	MPPT 80 600	MPPT 100 600
Electrical Specifications		
Max PV array open circuit voltage	600 V	600 V
MPPT voltage range	195 to 510 VDC	195 to 510 VDC
PV array operating voltage	195 to 550 V	195 to 550 V
Max. array short circuit current at STC	28 A	35 A
Max. input operating current	23 A	29 A
Max. output power	4800 W (nominal 48 V systems)	6000 W (nominal 48 V systems)
Nominal battery voltage	24 and 48 VDC	24 and 48 VDC
Battery voltage operating range	16 to 67 VDC	16 to 67 VDC
Max. output charge current	80 A	100 A
Charger regulation method	Three-stage (bulk, absorption, float) plus manual equalization Two-stage (bulk, absorption) plus manual equalization	
Supported battery types	Flooded, GEL, AGM, Lithium-ion, Custom	
Efficiency		
Max. power conversion efficiency	95% (nominal 48 V), 92% (nominal 24 V)	
General Specifications		
Power consumption, night time	< 1 W	
Battery temperature sensor	Included	
Auxiliary output	Dry contact switching up to 60 VDC, 30 VAC, 8 A	
Enclosure material	Enclosure material: Indoor, ventilated, aluminium sheet metal chassis	
Knockout dimensions	44.0 mm, 35.0 mm, 28.2 mm, and 22.2 mm knockouts for 1-1/4, 1, 3/4, and 1/2 inch trade size fittings	
IP degree of protection	IP20	
Product weight	13.5 kg (29.8 lb)	
Shipping weight	20.4 kg (45 lb)	
Product dimensions (H x W x D)	76.0 x 22.0 x 22.0 cm (30.0 x 8.6 x 8.6 in)	
Shipping dimensions (H x W x D)	113.39 x 28.68 x 31.90 cm (44.64 x 11.29 x 12.56 in)	
Ambient air temperature for operation	-20 °C to 65 °C (-4 °F to 149 °F), power derating above 40 °C	
Storage temperature range	-40 °C to 85 °C (-40 °F to 185 °F)	
Operating altitude	Sea level to 2000 m (6562 ft)	
System network and remote monitoring	Available with Insight Energy Management	
Warranty	Please refer to our website, SESolar.com for the latest version of the warranty statement.	
Part number	865-1032	865-1034
Regulatory Approvals		
Safety	CSA certified (UL1741, CSA 107.1) and CE marked for the Low-voltage Directive (EN50178)	
EMC	FCC and Industry Canada (Class B), CE marked for the EMC Directive (EN61000-6-1, -6-3)	
Compatible Products List		
XW Pro hybrid inverter	XW Pro 6848 120/240 VAC (865-6848-21), XW Pro 8548 230 VAC 865-8548-55)	
XW+ hybrid inverter	XW+ 8548 230 VAC (865-8548-61)	
SW IEC (230 VAC)	SW 4024 230 VAC (865-4024-55), SW 4048 230 VAC (865-4048-55)	
SW UL (120/240 VAC)	SW 4024 120/240 VAC (865-4024-21), SW 4048 120/240 VAC (865-4048-21)	
XW Power Distribution Panels	865-1015-01, 865-1014-01	
XW Mini Power Distribution Panels	865-1013-01	
MPPT Disconnect RS and RS initiator Switch	865-1036, 865-1039	
Insight Energy Management	InsightHome (865-0330), InsightFacility (865-0335), Insight	
Conext System Control Panel	865-1050-01	
Conext Automatic Generator Start	865-1060-01	
Conext Battery Monitor	865-1080-01	